



Kao Collins

BAR

TECHNICAL SPECIFICATIONS

Print Module

| | 4" X-Bar | 9" X-Bar |
|-----------------------------------|---|---|
| Print array | 2 arrays of 3 Samba G3L printheads | 1 array of 6 Samba G3L printheads |
| Nozzles per array | 5632 | 11264 |
| Print width | 119.2 mm (4.6933 inches) | 238.4 mm (9.386 inches) |
| Cross process dpi | 1200 | 1200 |
| Process resolution | 300/600/600i/1200 dpi | 300/600/1200 |
| Module dimensions & weight | Height 20", Depth 7.5", Width 7.5", 45lbs | Height 11.8, Depth 9.3", Width 16", 54lbs |
| Fluid station dimensions & weight | Height 40", Depth 26", Width 24", 200lbs | Height 40", Depth 26", Width 24", 200lbs |
| Monochrome system | black, spot color | black, spot color |
| Speed | 1000 fpm @ 1200 x 600 dpi | 1000 fpm @ 1200 x 300 dpi |
| Controller interface | Windows 7/10 | Windows 7/10 |
| Variable data | Yes | Yes |

Controller Product Specs

| | |
|---------------------|---|
| Power requirements | 90-264VAC, 50/60 Hz |
| Physical dimensions | Height 47", Depth 39", Width 24", 300 lbs |
| User interface | 24" LCD Touch Screen + mouse & keyboard |
| Networking | TCP/IP connection, Windows 7/10 |
| Speeds | Up to 1000 fpm (300 mpm) |

Benefits

Cost savings: Retrofit 8 Kodak Versamark Printing Systems with X-BAR Print Modules for less than the cost of purchasing one new printer.

Reduce downtime: Keep your printer up and running longer by eliminating lengthy periods of downtime.

Better DPI: Produce higher-quality print jobs at a lower cost.

In control: Manage up to 32 existing Kodak Versamark Printing Systems or 16 all-new X-Bar Print Modules with the universal controller.

Find out more at kaoxbar.com

Request a demo to see the Kao Collins X-BAR Print Module and Controller live in action.